



EPIC

TECHNICAL SPECS

SHUTTER SYNC PULSE
IN/OUT, RS170A GENLOCK

HD-SDI OUTPUT @ 720P,
1080P OR 2K 4:2:2 OR 4:4:4

RED INSPIRED FLUT® COLOR SCIENCE
FOR EASY EXPOSURE AND COLOR

OPTION OF BOMBEVF, 2.8", 5" OR 9" 24 BIT
WIDE COLOR GAMUT TOUCHSCREEN LCD

2K MIND NUMBING 225 FPS
SLOW MOTION @ 2K

WIDE RANGE ISO 200-12800 FOR
SHOOTING IN ANY LIGHT

5K INDUSTRY LEADING 5K
RESOLUTION @ 120 FPS

REDCODE® 30-250 FOR VARIABLE
COMPRESSION SELECTION

13.5+ STOPS OF
DYNAMIC RANGE

ONBOARD HDMI PC
MONITOR OUTPUT

3D 3D READY-INCLUDING
SHUTTER SYNC, REVERSIBLE
SENSOR SCAN FOR PRISM RIGS
AND 3D SPECIFIC METADATA
AND MENUS

BUILT IN TIMELAPSE
CONTROL

HOT SWAPPABLE BATTERIES
FOR CONTINUOUS RECORDING

ONBOARD REDCODE RAW
RECORDING TO 16/64GB
COMPACT FLASH

ONBOARD REDCODE® RAW
LOSSLESS 2.5:1 RECORDING
TO 256GB & 512GB SSD

OPTIONAL H.264
RECORDING MODULE

5LB SUPER LIGHT 5
POUND CAMERA BODY

POWER CONSUMPTION
LESS THAN 60W **60W**

MODULAR ARCHITECTURE ALLOWS
INFINITE CONFIGURATION & UPGRADING

HIGH EFFICIENCY SEALED COOLING SYSTEM FOR MOISTURE AND DUST PROTECTION

2CH. OR 4CH. AUDIO LINE/MIC IN 24BIT
WITH 48KHZ. SAMPLING

FULL SIZED XLR AND AES DIGITAL INPUTS
WITH PRO I/O MODULE

REDMOTE™ WIRELESS -
CONTROL ONE OR
MORE CAMERAS

REMOTE CONTROL VIA
REDLINK (WIRELESS),
WI-FI, RS422 & GIG-E



REDMOTE™ PRO (SHOWN)